

## APPLYING THE FUZZY INFERENCE USING WABL DEFUZZIFICATION METHOD TO FUZZY CONTROLS\*

Reyhan Shikhliinskaya<sup>1</sup>, Sinem Peker<sup>2</sup> and Efendi Nasibov<sup>3</sup>

<sup>1</sup>Baku State University, Institute of Applied Mathematics, Baku, Azerbaijan  
reyhanshikhli@gmail.com

<sup>2</sup>Yasar University, Faculty of Science and Letters, Bornova, Izmir, Turkey

<sup>3</sup>Dokuz Eylul University, Faculty of Science, Buca, Izmir, Turkey

**Abstract.** This paper presents new fuzzy inference rules based on the WABL deactivation method and applies to fuzzy controls. The package of applied programs is worked out on the base of proposed algorithms. The obtained in the form of visual-interactive graphs results are compared with known ones.

**Keywords:** fuzzy logic, inference system, WABL defuzzification.

**AMS Subject Classification:** 93C42 - Fuzzy control systems

### 1. Introduction.

Fuzzy simulation nowadays is one of the intensive directions of researches in control and decision making fields. Fuzzy simulation, i.e. fuzzy theory-based program models enable to get more adequate results in the field of control of engineering systems. Their application field becomes more and more from year to year: domestic electric equipments, cameras, video cameras, industrial robots and others are converted to fuzzy logic based working principles [1-3].

Sometimes to use instead of fuzzy parameters their defuzzification, i. e. exact representative is possible from the point of view of model's adequacy and this considerably simplifies the calculations. There are different defuzzification methods: COA (Center of Area), MOM (median of maximum), OWA (Ordered Weighted Average), WABL (Weighted Average Based on Levels) and i.s.[6]. To use this or other defuzzification method depends on the statement of the problem.

This paper presents new fuzzy inference rules based on the WABL deactivation method and applies to fuzzy controls. We first give a brief description of the method [7-9].

### 2. The fuzzy inference by using WABL defuzzification method

Let the fuzzy number  $\tilde{A}$  be given by  $L-R$  description, i.e.

---

\* Работа была представлена на семинаре Института Прикладной Математики 11.12.2018

$$\tilde{A} = \bigcup_{\xi \in [0,1]} (\xi, A^\xi).$$

hear  $A^\xi = [L_A(\xi), R_A(\xi)] = \{t \in E \mid L_A(\xi) \leq t \leq R_A(\xi)\}$ ,  $A^1 \neq \emptyset$  and  $L_A(\xi) = \mu_\uparrow^{-1}(\xi)$ ,  $R_A(\xi) = \mu_\downarrow^{-1}(\xi)$ .  $\mu_\uparrow^{-1}$  and  $\mu_\downarrow^{-1}$  define left and right sides of a fuzzy number correspondingly.

**Definition.** When we say averaged representative of fuzzy number or WABL defuzzification we mean the following quantity:

$$I_w(A) = c_L \int_0^1 L_A(\xi) p(\xi) d\xi + c_R \int_0^1 R_A(\xi) p(\xi) d\xi \quad (1)$$

Where  $c_L$  and  $c_R$  indicate the importance degree of the left and right hand sides, respectively, by operating on fuzzy members and

$$c_L \geq 0, \quad c_R \geq 0:$$

$$c_L + c_R = 1$$

$p(\xi)$  - is the distribution function of importance degrees:

$$P : [0,1] \rightarrow E_+ \equiv [0, +\infty] \text{ and}$$

$$\int_0^1 p(\xi) d\xi = 1$$

We can show that a general form of the function  $p(\xi)$  is as follows:

$$p(\xi) = k\xi^{k-1}, \quad k \geq 0. \quad (2)$$

The WABL defuzzification method has the following properties:

1. WABL method is more general. For some class of fuzzy numbers we can select the parameters  $c_L$ ,  $c_R$ , and  $p(\xi)$  so that the result obtained by WABL defuzzification method coincides with the result obtained by an other defuzzification methods.

2. WABL defuzzification method is additive, i.e.:

$$I_w(A + B) = I_w(A) + I_w(B)$$

This method enables to take into account the expert's strategy in a model.

3. If the result of defuzzification doesn't satisfy the experts by changing  $C_L$ ,  $C_R$ , and  $p(\xi)$  parameters he may change defuzzification number or slide it arbitrarily to the left or right hand side.

Now we give the stages of logic inference rules based on WABL defuzzification method.

1. Organization of rules base for logic inference rules;  
 2. Fuzzification of input and output variables, i.e. construction of fuzzy sets  $\mu_{k_i}(x)$ ,  $i = \overline{1, n}$  and  $\mu_{l_j}(x)$ ,  $j = \overline{1, m}$  describing the  $k_i$  input fuzzy and  $l_j$  output fuzzy states;

3. Calculation of validity degree of entrance of  $x = \bar{x}$  exact input estimate to the fuzzy input estimates set  $\mu_{k_i}(x)$ ,  $i = \overline{1, n}$ . Denote this validity degrees by  $\bar{k}_i$ :  $\bar{k}_i = \mu_{k_i}(\bar{x})$ ,  $i = \overline{1, n}$ ;

4. Defuzzification of  $l_j$  output fuzzy subsets by WABL method (determination of  $I_W(l_j)$ ),  $j = \overline{1, m}$ ;

5. Addition of the exact input value of defuzzification results with the coefficients equal to validity degree;

$$I_W = \sum_{i=1}^n \sum_{j=1}^m \bar{k}_i I_W(l_j)$$

**Example.** [4-5]. Let's see the functioning fuzzy inference system controlling a fan of room conditioner. Conditioner's work keeps optimal temperature in the room. Applying a new method let's see what changes will occur in the work of the expert system.

Assume that by changing rotation speed of the fan. We can change the temperature of the room. let's construct the working algorithm of the conditioner step by step. We first give rules base for the working algorithm. Notice that the organization of rules base in a subjective process and depends on the desire of the expert.

Rules base:

- 1) If the temperature of the room is lover, the rotation speed of a fan is lover;
- 2) If the temperature of the room is middle, the rotation speed of a fan is middle;
- 3) If the temperature of the room is higher, the rotation speed of a fan is higher;

As we see there are six fuzzy terms sets in rules base. Three of them: "lower temperature", "middle temperature" and "higher temperature" are input fuzzy parameters; the other ones: "lover speed", "middle speed", "higher speed" are output fuzzy parameters.

We are to define membership functions for fuzzy subsets determined in fuzzy input value set of temperature and in fuzzy output values set of rotation speed of the fan in defuzzification step of fuzzy variables.

Let's define membership function for the "lover", "middle" and "higher" fuzzy subsets of temperature (fig. 1).




Fig.1. The "lower", "middle" and "higher" fuzzy subsets of temperature and for rotation speed of a fan.

$$\mu_{t_{lower}}(t) = \begin{cases} 1, & t \leq 12 \\ \frac{20-t}{8}, & 12 < t < 20 \\ 0, & t \geq 20 \end{cases} \quad (3)$$

$$\mu_{t_{omiddle}}(t) = \begin{cases} 0, & t < 12 \text{ ve } t > 30 \\ \frac{t-12}{8}, & 12 \leq t < 20 \\ \frac{30-t}{10}, & 20 \leq t \leq 30 \end{cases} \quad (4)$$

$$\mu_{t_{higher}}(t) = \begin{cases} 0, & 0 < t < 20 \\ \frac{t-20}{10}, & 20 \leq t < 30 \\ 1, & 30 \leq t < 60 \end{cases} \quad (5)$$

Now let's define fuzzy subsets for output variables. Assume that the rotation speed of the fan varies from 0 and 1000 rot/min. then we'll define for this speed the "lower", "middle" and "higher" fuzzy subsets and their membership functions as follows (see fig.4,5 and 3):

$$\mu_{v_{lower}}(t) = \begin{cases} 1, & 0 < v < 200 \\ \frac{400-v}{200}, & 200 \leq v \leq 400 \\ 0, & 400 < v < 1000 \end{cases} \quad (6)$$

$$\mu_{v_{middle}}(t) = \begin{cases} 0, & 0 < v < 200 \\ \frac{v-200}{200}, & 200 \leq v < 400 \\ \frac{600-v}{200}, & 400 \leq v \leq 600 \end{cases} \quad (7)$$

$$\mu_{v_{higher}}(t) = \begin{cases} 0, & 0 < v < 400 \\ \frac{v-400}{200}, & 400 \leq v < 600 \\ 1, & 600 \leq v < 1000 \end{cases} \quad (8)$$

3. Let's see the process of definition of rotation speed of a fan depending a temperature of the room by fuzzy expert system. Assume the room's temperature is  $t = 22^{\circ}C$ .

The first calculate the degree of  $t = 22^{\circ}C$  value to fuzzy subset (1) - (3):

$$\begin{aligned} \mu_{t_{lower}}(22) &= 0 \\ \mu_{t_{middle}}(22) &= 0,8 \\ \mu_{t_{higher}}(22) &= 0,2 \end{aligned} \quad (9)$$

In this step defuzzificate fuzzy output subset (6) - (8) by WABL method.

Let's write the increasing and diminishing parts in fuzzy set (7) according to levels:

$$L_{v_{lower}}(\xi) = 0,$$

$$R_{v_{lower}}(\xi) = -200\xi + 400$$

Take them into account in (1):

$$I_W(v_{lower}) = (1 - c_L) \int_0^1 (-200\xi + 400)(k+1)\xi^k d\xi = -200c_L \frac{k+3}{k+2} - 200 \frac{k+1}{k+2} + 400. \quad (10)$$

For fuzzy set (7)-(8):

$$L_{v_{middle}}(\xi) = 200\xi + 200,$$

$$R_{v_{middle}}(\xi) = -200\xi + 600,$$

$$I_W(v_{middle}) = c_L \int_0^1 (200\xi + 200)(k+1)\xi^k d\xi + (1 - c_L) \int_0^1 (-200\xi + 600)(k+1)\xi^k d\xi = -400c_L \frac{1}{k+2} - 200 \frac{k+1}{k+2} + 600, \quad (11)$$

$$L_{v_{higher}}(\xi) = 200\xi + 400, \quad R_{v_{higher}}(\xi) = 1000,$$

$$I_W(v_{higher}) = c_L \int_0^1 (200\xi + 400)(k+1)\xi^k d\xi + (1 - c_L) \int_0^1 1000(k+1)\xi^k d\xi = -200c_L \frac{2k+5}{k+2} + 1000 \quad (12)$$

Now multiply the averaged representative of input fuzzy subsets  $I_i$  by corresponding constants equal to  $k_i$  and summarize them [5], [6]:

$$I_W = 0 \cdot I_W(l_{lower}) + 0.8 \cdot I_W(l_{middle}) + 0.2 \cdot I_W(l_{higher}) = 0.8 \cdot 400 + 0.2 \cdot 766 = 473.2 \quad (13)$$

So if temperature will be  $22^{\circ}\text{C}$  the expert will adopt the rotation speed of a fan 473.2 rot/min.

Each time when we result of logical inference is required the above mentioned operations are carried out by the same order. In dynamic control systems this sequence is performed periodically.

It each time we'll mark the pair  $(t, v)$  in coordinate surface we'll obtain a graph of the dependence of rotation speed .




Fig. 2. The algorithm of work of fuzzy expert system




Fig. 3. The temperature changing regime by  $t_0 = 37, c_L = 0.3, k = 1000 (p(\xi) = 1001\xi^{1000})$




Fig. 4. The temperature changing regime by  $t_0 = 7, c_L = c_R = 1/2, k = 1 (p(\xi) = 2\xi)$

It was proved that fuzzy logic conditioners provide the less vibration of temperature and saves much electric power. The work of fuzzy logic based systems in dynamic processes is more effective than work of control circuits working on an ordinary thermostat.

**3. Conclusion.** The other expert system may determine the rotation speed by another way. But by changing the parameters  $c_L, c_R$  and  $p(\xi)$  in WABL defuzzification formula [3]. We can arbitrarily change the rotation speed of a fan within its definition domain. The comparing the results of the work of our expert system and the expert system given in [1] with different values of input parameters is shown on the fig. 3-4. The optimal temperature to what the temperature of the room tents as a result of air conditioner working is defined by itself system. In our case changing the values of  $c_L$  and  $c_R$ . The optimal temperature of the room may be changed.

### References

1. Aliev, F.A., Niftiyev, A.A., Zeynalov, J.I., Optimal synthesis problem for the fuzzy systems in semi-infinite interval, Appl. Comput. Math., 10 (1), 2011, pp.97-105.
2. Aliev, F.A., Niftiyev, A.A., Zeynalov, J.I., Optimal synthesis problem for the fuzzy systems, Optimal Control, Applications and Methods, 2011, V.32, N.6, pp.660-677.
3. Aliev, F.A., Niftiyev, A.A., Zeynalov, J.I., Methods to Solution of the Fuzzy Optimal Control Problems, Baku, "Elm", p.200.
4. Korneev, V.V., Database. Intellectual processing of information, Decisions in vague conditions, Moscow, Knowledge, 2001, pp.255-290



5. Leonenkov, A., Fuzzy Modeling in MATLAB and Fuzzy TECH., BHV, Petersburg, 2003, p.73.
6. Nasibov, E.N., Methods of Processing Fuzzy Information in Decision-making Tasks, Baku, Elm, 2000, p.260.
7. Nasibov, E.N., On one task of identifying the system states using fuzzy values of informative features, Riga, Automation and Computer Engineering, No. 2, 2003, p. 33-40
8. Nasibov E.N., Shikhlinская R.Y., Set-up of WABL-aggregation parameters for finding the gravity centre of fuzzy number of polynomial form, Automatic Control and Computer Sciences, 37 (2003), No.6.
9. Shikhlinская R.Y. The relation between averaging representative and weight century, Baku, the 1-st International Conference on Control and Optimization with Industrial Applications.

## **Применение нечеткого логического вывода с дефазификационным методом WABL к нечеткому управлению**

**Рейхан Шихлинская<sup>1</sup>, Синем Пекер<sup>2</sup> и Эфенди Насибов<sup>3</sup>**

<sup>1</sup>Бакинский Государственный Университет, Институт Прикладной Математики,  
Баку, Азербайджан  
reyhanshikhli@gmail.com

<sup>2</sup>Университет Яшар, Математический факультет, Измир, Турция

<sup>3</sup>Докуз Ейлульский Университет, факультет Компьютерных Наук, Измир, Турция

### **РЕЗЮМЕ**

В статье рассмотрен метод дефазификации WABL, построена система нечеткого логического вывода на основе метода WABL и применена к нечетким регуляторам. Полученные результаты, т.е. режим изменения температуры в комнате в зависимости от скорости вращения вентилятора представлены в виде визуально-интерактивных графиков и сравнены с другими методами.